

View Online at <https://aerobasegroup.com/nsn/5930-00-636-1425>

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

1.000 inches

Overall Height:

0.628 inches

Body Diameter:

0.640 inches

Body Height:

0.363 inches

Unthreaded Mounting Hole Diameter:

0.115 inches

Distance Between Mounting Facility Centers:

0.812 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

175.0 degrees celsius and 40.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load third voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

145.00 actuation point degrees fahrenheit and 125.00 deactuation point degrees fahrenheit and 20.00 differential point degrees celsius

Contact Voltage Rating In Volts:

30.0 dc at sea level third voltage

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0