

View Online at <https://aerobasegroup.com/nsn/5930-00-636-1425>

**Hazardous Locations/environmental Protection:**

Moisture proof

**Overall Length:**

1.000 inches

**Overall Height:**

0.628 inches

**Body Diameter:**

0.640 inches

**Body Height:**

0.363 inches

**Unthreaded Mounting Hole Diameter:**

0.115 inches

**Distance Between Mounting Facility Centers:**

0.812 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

175.0 degrees celsius and 40.0 degrees celsius

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load third voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

145.00 actuation point degrees fahrenheit and 125.00 deactuation point degrees fahrenheit and 20.00 differential point degrees celsius

**Contact Voltage Rating In Volts:**

30.0 dc at sea level third voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0