## NSN 5930-00-636-2878

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-2878

Body Style:
Hole mounted
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.750 inches
Body Length:
1.070 inches
Body Width:
0.560 inches
Body Height:
0.810 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.500 inches
Actuator Style:
Round
Actuator Diameter:
0.115 inches
Actuator Height:
0.190 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
0.5 grams
Switch Actuating Force:
4.0 grams
Actuator Movement:
Between 20.0 pretravel degrees and 20.0 overtravel degrees and 35.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive ac
Special Features:
Switch mtd on circular flange 2.500 in. Diameter with 3 mtg holes spaced 120 degrees apart
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5930-00-636-2878

Sensitive Switch - Page 2 of 2



em			

No

Fiig:

A053a0