NSN 5930-00-636-3180

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-3180 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Salt water resistant **Overall Length:** 1.625 inches **Overall Height:** 1.993 inches **Overall Width:** 0.562 inches **Bushing Length:** 0.562 inches **Body Length:** 0.828 inches **Body Width:** 1.203 inches **Body Height:** 0.562 inches **Case Material:** Plastic **Actuator Style:** Round **Actuator Diameter:** 0.312 inches **Actuator Adapter Style:** Pushbutton **Adapter Bushing Length:** 0.562 inches **Maximum Voltage Rating In Volts:** 125.0 ac **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

NSN 5930-00-636-3180 Sensitive Switch - Page 2 of 2



Switch Release Force:
3.0 ounces
Switch Actuating Force:
Between 6.0 ounces and 12.0 ounces
Actuator Movement:
Between 0.052 pretravel inches and 0.219 overtravel inches and 0.047 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive ac
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0