

View Online at <https://aerobasegroup.com/nsn/5930-00-636-3180>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Salt water resistant

Overall Length:

1.625 inches

Overall Height:

1.993 inches

Overall Width:

0.562 inches

Bushing Length:

0.562 inches

Body Length:

0.828 inches

Body Width:

1.203 inches

Body Height:

0.562 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.312 inches

Actuator Adapter Style:

Pushbutton

Adapter Bushing Length:

0.562 inches

Maximum Voltage Rating In Volts:

125.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

Between 6.0 ounces and 12.0 ounces

Actuator Movement:

Between 0.052 pretravel inches and 0.219 overtravel inches and 0.047 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0