

View Online at <https://aerobasegroup.com/nsn/5930-00-636-3274>

Overall Length:

4.968 inches

Body Diameter:

0.625 inches

Body Length:

3.500 inches

Overall Diameter:

1.578 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Bulb Length:

3.500 inches

Bulb Diameter:

0.625 inches

Temperature Sensing Element Type:

Bulb

Mounting Facility Circle Radius:

1.250 inches

Operating Temperature Rating:

Between 100.0 degrees fahrenheit and 750.0 degrees fahrenheit

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Threaded stud

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable, preset and actuation point adjustable, preset

Contact Adjustment Range:

+100.00/+750.00 actuation point degrees fahrenheit and +100.00/+750.00 deactuation point degrees fahrenheit

Contact Stimulus Rating:

0.10 differential point degrees fahrenheit and 525.00 actuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Special Features:

Minus 65 degrees f under-run to 1500 degrees f over-run safe temperature range

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Hex nut surfaces silver

Precious Material:

Silver

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0