NSN 5930-00-636-3568

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-3568

First Flat Length:

0.500 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

5

Knob Specificationial Markings:

Arrow sign

Longest Horizontal Distance Between Mounting Centers:

1.625 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.625 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

34 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 dc at sea level

Mounting Facility Pattern:

Two position diagonal single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

NSN 5930-00-636-3568

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0