

View Online at <https://aerobasegroup.com/nsn/5930-00-636-4407>

Overall Length:

4.500 inches

Body Diameter:

0.620 inches

Body Length:

3.562 inches

Unthreaded Mounting Hole Diameter:

0.221 inches

Bulb Length:

3.562 inches

Bulb Diameter:

Between 0.616 inches and 0.624 inches

Longest Horizontal Distance Between Mounting Centers:

1.082 inches

Shortest Horizontal Distance Between Mounting Centers:

0.541 inches

Longest Vertical Distance Between Mounting Centers:

0.625 inches

Temperature Sensing Element Type:

Bulb

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

5.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

200.00 actuation point degrees fahrenheit and -100.00 deactuation point degrees fahrenheit and 1.00 differential point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level third voltage

Special Features:

Minum 100 degrees f under-run to 1000 degrees f over-run safe temperature range

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Cylindrical w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0