NSN 5930-00-636-4960

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-4960 **Thread Class:** 2b 2nd mounting facility **Overall Length:** 6.375 inches **Overall Height: 4.375** inches **Overall Width:** 2.916 inches **Unthreaded Mounting Hole Diameter:** 0.312 inches 1st mounting facility and 0.317 inches 1st mounting facility **Distance Between Mounting Facility Centers:** 3.812 inches 1st mounting facility **Individual Section Quantity:** 12 **Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 3.219 inches 2nd mounting facility **Longest Vertical Distance Between Mounting Centers:** 3.219 inches 2nd mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 single section front **Throw Quantity:** 2 single section front **Mounting Method:** Unthreaded hole 1st mounting facility and bracket 1st mounting facility **Features Provided:** Actuator knob and metallic inclosure Thready Qty Per Inch (tpi): 20 2nd mounting facility **Thread Size:** 0.250 inches 2nd mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Mounting Facility Pattern:** Two position in-line 1st mounting facility **Switch Actuator Indexing Position Quantity:** 12 single actuator **Terminal Type:**

Tab w/screw

NSN 5930-00-636-4960

Rotary Switch - Page 2 of 2



Contact	Switching	Action:
CUIILACL	SWILCIIIII	ACLIOII.

Breaks before makes single section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0