NSN 5930-00-636-4960

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-636-4960

Thread Class:

2b 2nd mounting facility

Overall Length:

6.375 inches

Overall Height:

4.375 inches

Overall Width:

2.916 inches

Unthreaded Mounting Hole Diameter:

0.312 inches 1st mounting facility and 0.317 inches 1st mounting facility

Distance Between Mounting Facility Centers:

3.812 inches 1st mounting facility

Individual Section Quantity:

12

Knob Manufacturer Code:

82121

Longest Horizontal Distance Between Mounting Centers:

3.219 inches 2nd mounting facility

Longest Vertical Distance Between Mounting Centers:

3.219 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

2 single section front

Mounting Method:

Unthreaded hole 1st mounting facility and bracket 1st mounting facility

Features Provided:

Actuator knob and metallic inclosure

Thready Qty Per Inch (tpi):

20 2nd mounting facility

Thread Size:

0.250 inches 2nd mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Two position in-line 1st mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Terminal Type:

Tab w/screw

NSN 5930-00-636-4960

Rotary Switch - Page 2 of 2



Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 2nd mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0