NSN 5930-00-642-2482

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-2482

Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.250 inches **Overall Height:** 1.875 inches **Overall Width:** 1.516 inches First Flat Length: 0.500 inches single actuator Flat Height: 0.188 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 1.500 inches single actuator **Nonturn Device Radius:** 0.531 inches at 10: 00 o'clock **Nonturn Device Type:** Tab at 10: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 3 each section rear **Throw Quantity:** 3 each section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 1000.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Makes before breaks each section rear **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-642-2482

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

5.0 amperes resistive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0