NSN 5930-00-642-9073

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-9073				
Hazardous Locations/environmental Protection: Dustproof				
Overall Height:				
4.312 inches				
Overall Width:				
3.188 inches				
Shaft Diameter:				
0.343 inches single actuator				
Shaft Length:				
1.719 inches single actuator				
Unthreaded Mounting Hole Diameter:				
0.213 inches single mounting facility				
Individual Section Quantity:				
1				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
3.750 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
1 single section front				
Throw Quantity:				
3 single section front				
Mounting Method:				
Bracket single mounting facility and unthreaded hole single mounting facility				
Contact Voltage Rating In Volts:				
125.0 dc at sea level				
Mounting Facility Pattern:				
Four position rectangular single mounting facility				
Switch Actuator Indexing Position Quantity:				
4 single actuator				
Shaft Type:				
Round single actuator				
Terminal Type:				
Tab, solder lug				
Contact Switching Action:				
Breaks before makes single section rear				
Switch Actuator Positioning Increment:				

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-642-9073

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0