NSN 5930-00-642-9219

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-9219
Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.373 inches and 0.377 inches
Overall Height:
0.518 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.391 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.087 inches and 0.090 inches
Actuator Style:
Dound

Round

Actuator Diameter:

Between 0.087 inches and 0.097 inches

Actuator Free Position Height:

Between 0.315 inches and 0.345 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.008 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes motor dc and 5.000 amperes resistive ac

NSN 5930-00-642-9219

Sensitive Switch - Page 2 of 2



i ei ii ii iai Tybe And Quantity.	Tε	rminal	Type	And	Quantity:	
-----------------------------------	----	--------	------	-----	-----------	--

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0