NSN 5930-00-642-9256

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-9256

Thread Class:

2b single mounting facility

Shaft Diameter:

0.218 inches single actuator

Shaft Length:

1.375 inches single actuator

Individual Section Quantity:

5

Knob Manufacturer Code:

56232

Longest Horizontal Distance Between Mounting Centers:

1.875 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

1 each section front

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

450.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

NSN 5930-00-642-9256

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load lowest ac voltage rating at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0