NSN 5930-00-642-9275

Hazardous Locations/environmental Protection:

Rotary Switch - Page 1 of 2

Watertight

Overall Height:



View Online at https://aerobasegroup.com/nsn/5930-00-642-9275

| 7.125 inches |
|---|
| Overall Width: |
| 6.250 inches |
| Shaft Length: |
| 1.125 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.406 inches single mounting facility |
| Individual Section Quantity: |
| 4 |
| Knob Manufacturer Code: |
| 81316 |
| Knob Manufacturer Part Number: |
| 5969-201pc22 |
| Longest Horizontal Distance Between Mounting Centers: |
| 3.250 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 3.000 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up symmetrical |
| Mounting Method: |
| Bracket single mounting facility |
| Features Provided: |
| Actuator knob and metallic inclosure |
| Contact Voltage Rating In Volts: |
| 120.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 8 single actuator |
| Shaft Type: |
| Rectangular/square, threaded hole single actuator |
| Square Shaft Size: |
| 0.375 inches single actuator |
| Terminal Type: |
| Tab w/screw |
| Contact Switching Action: |
| Breaks before makes each section front |
| Switch Actuator Positioning Increment: |
| 45.0 degrees single actuator |

NSN 5930-00-642-9275

Rotary Switch - Page 2 of 2



10.0 amperes resistive load ac at sea level

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0