## NSN 5930-00-642-9308

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-642-9308

| view Offilite at https://aerobasegroup.com/hsh/0550-00-042-5500                       |
|---|
| Hazardous Locations/environmental Protection:   |
| Dustproof and watertight  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:             |
| 6.000 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:              |
| 5.000 inches  |
| Body Length:  |
| 9.625 inches  |
| Body Width:   |
| 5.875 inches  |
| Body Height:  |
| 3.750 inches  |
| Switch Actuator Quantity:   |
| 3   |
| Actuator Inscription:   |
| Stop 3rd actuator   |
| Maximum Voltage Rating In Volts:  |
| 440.0 ac and 440.0 dc   |
| Nonpile-up Contact Arrangement:   |
| 2 two circuit, double break/double make, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:                                 |
| 5.000 amperes resistive dc and 5.000 amperes resistive ac                             |
| Terminal Type And Quantity:   |
| 8 screw   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A053a0  |