NSN 5930-00-642-9308

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-642-9308

| view Offilite at https://aerobasegroup.com/hsh/0550-00-042-5500 |
|---------------------------------------------------------------------------------------|
| Hazardous Locations/environmental Protection: |
| Dustproof and watertight |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 5.000 inches |
| Body Length: |
| 9.625 inches |
| Body Width: |
| 5.875 inches |
| Body Height: |
| 3.750 inches |
| Switch Actuator Quantity: |
| 3 |
| Actuator Inscription: |
| Stop 3rd actuator |
| Maximum Voltage Rating In Volts: |
| 440.0 ac and 440.0 dc |
| Nonpile-up Contact Arrangement: |
| 2 two circuit, double break/double make, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 5.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 8 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A053a0 |