NSN 5930-00-642-9330

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-9330

| Body Style: | | | | |
|---|--|--|--|--|
| Hole mounted | | | | |
| Hazardous Locations/environmental Protection: | | | | |
| Moisture resistant | | | | |
| Overall Length: | | | | |
| 4.406 inches | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: | | | | |
| 0.531 inches | | | | |
| Overall Height: | | | | |
| 1.250 inches | | | | |
| Overall Width: | | | | |
| 1.938 inches | | | | |
| Body Length: | | | | |
| 3.062 inches | | | | |
| Body Width: | | | | |
| 0.938 inches | | | | |
| Body Height: | | | | |
| 1.250 inches | | | | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | | | | |
| 0.812 inches | | | | |
| Actuator Style: | | | | |
| Round | | | | |
| Actuator Diameter: | | | | |
| 0.375 inches | | | | |
| Actuator Height: | | | | |
| 1.125 inches | | | | |
| Actuator Position-action Relationship: | | | | |
| Up position maintained and down position maintained and center position maintained | | | | |
| Actuator Position-locking Relationship: | | | | |
| Up position locked in and down position locked in and center position locked in and out | | | | |
| Actuator Color: | | | | |
| Red single actuator | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 120.0 dc | | | | |
| Inclosure Type: | | | | |
| Uninclosed | | | | |
| Mounting Method: | | | | |
| Unthreaded hole | | | | |
| Pile-up Contact Form Arrangement: | | | | |
| 2b 2nd position | | | | |

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc

NSN 5930-00-642-9330

Lever Switch - Page 2 of 2



| Precious | Material | And | Location: |
|----------|----------|------------|-----------|
| | | | |

Contacts palladium and contact surfaces silver

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0