NSN 5930-00-642-9330

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-642-9330

Body Style:				
Hole mounted				
Hazardous Locations/environmental Protection:				
Moisture resistant				
Overall Length:				
4.406 inches				
Center To Center Distance Between Mounting Facilities Parallel To Width:				
0.531 inches				
Overall Height:				
1.250 inches				
Overall Width:				
1.938 inches				
Body Length:				
3.062 inches				
Body Width:				
0.938 inches				
Body Height:				
1.250 inches				
Center To Center Distance Between Mounting Facilities Parallel To Height:				
0.812 inches				
Actuator Style:				
Round				
Actuator Diameter:				
0.375 inches				
Actuator Height:				
1.125 inches				
Actuator Position-action Relationship:				
Up position maintained and down position maintained and center position maintained				
Actuator Position-locking Relationship:				
Up position locked in and down position locked in and center position locked in and out				
Actuator Color:				
Red single actuator				
Maximum Voltage Rating In Volts:				
120.0 dc				
Inclosure Type:				
Uninclosed				
Mounting Method:				
Unthreaded hole				
Pile-up Contact Form Arrangement:				
2b 2nd position				

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc

NSN 5930-00-642-9330

Lever Switch - Page 2 of 2



Precious	Material	And	Location:

Contacts palladium and contact surfaces silver

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0