

View Online at <https://aerobasegroup.com/nsn/5930-00-642-9715>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

1.280 inches

**Body Width:**

0.530 inches

**Body Height:**

0.910 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Actuator Length:**

0.250 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.120 inches

**Actuator Width:**

0.290 inches

**Actuator Free Position Height:**

0.505 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, both positions maintained single switch unit

**Switch Release Force:**

3.0 ounces

**Switch Actuating Force:**

28.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.018 overtravel inches and 0.028 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0