

View Online at <https://aerobasegroup.com/nsn/5930-00-644-2540>

Thread Class:

2b

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

1.969 inches

Overall Height:

1.812 inches

Overall Width:

0.500 inches

Body Length:

1.594 inches

Body Width:

0.500 inches

Body Height:

1.812 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.138 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.469 inches and 1.531 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.219 inches and 0.281 inches

Actuator Height:

Between 0.344 inches and 0.406 inches

Actuator Free Position Height:

Between 0.344 inches and 0.406 inches

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

15.0 ounces

Actuator Movement:

Between 0.203 pretravel inches and 0.031 overtravel inches and 0.250 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes resistive ac

Special Features:

Flexible insulator

Thread Series Designator:

Unc

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0