## NSN 5930-00-644-2540



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-644-2540 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.969 inches **Overall Height:** 1.812 inches **Overall Width:** 0.500 inches **Body Length:** 1.594 inches **Body Width:** 0.500 inches **Body Height:** 1.812 inches **Case Material:** Metal **Unthreaded Mounting Hole Diameter:** 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.469 inches and 1.531 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.219 inches and 0.281 inches **Actuator Height:** Between 0.344 inches and 0.406 inches **Actuator Free Position Height:** Between 0.344 inches and 0.406 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole

Thready Qty Per Inch (tpi):

32

**Thread Size:** 

0.138 inches

## NSN 5930-00-644-2540

Sensitive Switch - Page 2 of 2

**Fiig:** A053a0



Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
15.0 ounces
Actuator Movement:
Between 0.203 pretravel inches and 0.031 overtravel inches and 0.250 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 10.000 amperes resistive ac
Special Features:
Flexible insulator
Thread Series Designator:
Unc
Terminal Type And Quantity:
3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No