

View Online at <https://aerobasegroup.com/nsn/5930-00-644-2551>

Thread Class:

2a single mounting facility

Thread Length:

0.230 inches single mounting facility and 0.270 inches single mounting facility

Overall Length:

Between 2.740 inches and 3.020 inches

Overall Height:

Between 1.219 inches and 1.531 inches

Overall Width:

Between 1.219 inches and 1.531 inches

First Flat Length:

0.430 inches single actuator

Flat Height:

0.213 inches single actuator and 0.223 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.630 inches single actuator

Individual Section Quantity:

3

Operating Temperature Range:

-55.0/+30.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 each section rear

Throw Quantity:

2 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Detent Rotational Torque Range:

+3.000/+8.000 inch-pounds single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and terminal surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0