## NSN 5930-00-644-2706

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-644-2706 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 2.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.812 inches **Overall Height:** 5.094 inches **Overall Width:** 1.250 inches **Body Width:** 1.250 inches **Body Height:** 2.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.125 inches **Actuator Style:** Round **Actuator Height:** 1.594 inches **Actuator Position-action Relationship:** Up position momentary and down position momentary and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Actuator Color:** Black single actuator **Maximum Voltage Rating In Volts:** 110.0 ac **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): **Pile-up Contact Form Arrangement:** 1b1k 1st position

**Thread Size:** 

0.112 inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive ac

## **NSN 5930-00-644-2706** Lever Switch - Page 2 of 2



Inread Series Designator:
Unc
Terminal Type And Quantity:
10 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0