## NSN 5930-00-644-2752

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-644-2752

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 1.562 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.750 inches single actuator **Overall Diameter:** 1.250 inches **Individual Section Quantity: Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Pole Quantity:** 2 single section front **Throw Quantity:** 3 single section rear **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 300.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator **Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-644-2752

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

200.0 milliamperes resistive load dc at sea level

**Style Designator:** 

Snap or line

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0