NSN 5930-00-644-2766

Sensitive Switch - Page 1 of 2

4 screw



View Online at https://aerobasegroup.com/nsn/5930-00-644-2766

Body Style:
Hole mounted
Overall Height:
2.562 inches
Overall Width:
2.625 inches
Actuator Length:
1.500 inches
Actuator Style:
Leaf
Actuator Free Position Height:
1.937 inches
Housing Height:
2.875 inches
Housing Length:
4.000 inches
Housing Width:
2.562 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.875 inches
Maximum Voltage Rating In Volts:
400.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
18
Thread Size:
0.312 inches
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
4.0 inch-ounces
Switch Actuating Force:
232.0 inch-ounces
Actuator Movement:
Between 45.0 pretravel degrees and 13.0 overtravel degrees and 32.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes resistive ac
Thread Series Designator:
Unc
Terminal Type And Quantity:

NSN 5930-00-644-2766

Sensitive Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0