

View Online at <https://aerobasegroup.com/nsn/5930-00-644-3013>

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.062 inches

Overall Height:

1.406 inches

Overall Width:

1.531 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.156 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Nonturn Device Radius:

0.531 inches at 10:30 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 10:30 o'clock

Operating Temperature Range:

-25.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 2nd section rear

Throw Quantity:

5 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

270.0 degrees from nonturn device single actuator

Rotor Through Connection Quantity:

2 2nd section

Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Precious Material And Location:

Contacts and rotor surfaces silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0