NSN 5930-00-646-4360

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-646-4360 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 0.840 inches **Overall Height:** 2.106 inches **Overall Width:** 0.719 inches **Bushing Length:** 0.470 inches **Body Length:** 0.840 inches **Body Width:** 0.719 inches **Body Height:** 0.946 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Diameter:** 0.240 inches **Actuator Height:** 0.690 inches **Actuator Position-action Relationship:** Up position momentary and down position maintained and center position momentary **Maximum Voltage Rating In Volts:** 250.0 ac and 30.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 32 **Thread Size:**

Nonpile-up Contact Arrangement:

0.469 inches

2 pole, double throw, both positions maintained single switch unit

NSN 5930-00-646-4360

Toggle Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0