

View Online at <https://aerobasegroup.com/nsn/5930-00-646-4619>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Flame resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.850 inches

Body Width:

0.092 inches

Body Height:

0.359 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.088 inches

Actuator Style:

Round

Actuator Free Position Height:

0.375 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

5.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 5.000 amperes resistive ac

Test Data Document:

96906-ms25085 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0