# NSN 5930-00-647-2652

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-647-2652

# Thread Class:

2a single mounting facility

# Thread Length:

0.375 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

1.750 inches

## **Overall Height:**

1.500 inches

## **Overall Width:**

1.312 inches

## First Flat Length:

0.375 inches single actuator

## Flat Height:

0.219 inches single actuator

## Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.875 inches single actuator

# Individual Section Quantity:

1

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 single section rear

#### **Throw Quantity:**

3 single section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## Features Provided:

Metallic inclosure

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

15.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

4 single actuator

#### Shaft Type:

Round, flatted single actuator

# NSN 5930-00-647-2652

Rotary Switch - Page 2 of 2



**Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes single section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator **Contact Load Current Rating:** 150.0 milliamperes resistive load ac at sea level **Special Features:** W/locking device, one dummy terminals **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0