

View Online at <https://aerobasegroup.com/nsn/5930-00-647-3080>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof and oiltight and watertight

**Overall Length:**

4.940 inches

**Overall Height:**

2.100 inches

**Overall Width:**

2.310 inches

**Case Material:**

Metal

**Actuator Length:**

1.500 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.750 inches

**Actuator Roller Width:**

0.500 inches

**Housing Length:**

4.940 inches

**Housing Width:**

2.250 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

4.219 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Width:**

1.812 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

3 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

125.0 ounces

**Actuator Movement:**

11.0 pretravel degrees and 70.0 overtravel degrees and 4.0 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac

**Special Features:**

Spring return of switch lever

**Terminal Type And Quantity:**

12 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0