NSN 5930-00-647-3080

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-647-3080

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and oiltight and watertight
Overall Length:
4.940 inches
Overall Height:
2.100 inches
Overall Width:
2.310 inches
Case Material:
Metal
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.500 inches
Housing Length:
4.940 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
3 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:
125.0 ounces
Actuator Movement

Actuator Movement.

11.0 pretravel degrees and 70.0 overtravel degrees and 4.0 differential degrees

NSN 5930-00-647-3080

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac

Special Features:

Spring return of switch lever

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0