

View Online at <https://aerobasegroup.com/nsn/5930-00-647-3080>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and oiltight and watertight

Overall Length:

4.940 inches

Overall Height:

2.100 inches

Overall Width:

2.310 inches

Case Material:

Metal

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.500 inches

Housing Length:

4.940 inches

Housing Width:

2.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

3 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

125.0 ounces

Actuator Movement:

11.0 pretravel degrees and 70.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 15.000 amperes resistive ac and 3.000 amperes inductive ac

Special Features:

Spring return of switch lever

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0