## NSN 5930-00-649-9368

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-649-9368

**Thread Class:** 

2a single mounting facility

**Thread Length:** 

0.164 inches single mounting facility

**Overall Length:** 

4.250 inches

First Flat Length:

0.562 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.250 inches single actuator

**Overall Diameter:** 

2.812 inches

**Individual Section Quantity:** 

2

**Knob Manufacturer Code:** 

82121

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Facility Circle Radius:** 

1.812 inches single mounting facility

**Mounting Method:** 

Threaded stud single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, square single actuator

**Square Shaft Size:** 

0.250 inches single actuator

**Terminal Type:** 

Tab w/screw

## NSN 5930-00-649-9368

Rotary Switch - Page 2 of 2



| $\mathbf{c}$ | nnf  | act | SW | itch | ina   | ı Ac | tior | ٠. |
|--------------|------|-----|----|------|-------|------|------|----|
| U            | וווכ | acı | ЭW | ILCI | IIIIU | IAC  | เเบเ | ı. |

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0