

View Online at <https://aerobasegroup.com/nsn/5930-00-650-1657>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof and weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.998 inches and 1.002 inches

Body Length:

1.938 inches

Body Width:

0.688 inches

Body Height:

0.953 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

Between 0.140 inches and 0.147 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.560 inches and 1.720 inches

Actuator Roller Diameter:

0.370 inches

Actuator Roller Width:

0.150 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Switch Actuating Force:

Between 10.0 ounces and 15.0 ounces

Actuator Movement:

Between 0.188 pretravel inches and 0.500 overtravel inches and 0.125 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 5.000 amperes motor ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0