

View Online at <https://aerobasegroup.com/nsn/5930-00-650-1657>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof and weatherproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.998 inches and 1.002 inches

**Body Length:**

1.938 inches

**Body Width:**

0.688 inches

**Body Height:**

0.953 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.140 inches and 0.147 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

Between 1.560 inches and 1.720 inches

**Actuator Roller Diameter:**

0.370 inches

**Actuator Roller Width:**

0.150 inches

**Actuator Adapter Style:**

Roller arm

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Switch Actuating Force:**

Between 10.0 ounces and 15.0 ounces

**Actuator Movement:**

Between 0.188 pretravel inches and 0.500 overtravel inches and 0.125 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 5.000 amperes motor ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0