NSN 5930-00-650-1659 Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-650-1659
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.953 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.093 inches
Actuator Adapter Style:
Roller arm
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
16.0 ounces
Switch Actuating Force:
32.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.005 overtravel inches and 0.030 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive dc and 10.000 amperes inductive dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000
amperes inductive ac and 5.000 amperes motor ac
Terminal Type And Quantity:
3 screw
Shelf Life:

NSN 5930-00-650-1659

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0