# NSN 5930-00-651-2345

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-651-2345

# Thread Class:

2a single mounting facility

# Thread Length:

0.469 inches single mounting facility

# Hazardous Locations/environmental Protection:

Dustproof

#### **Overall Length:**

2.648 inches

#### First Flat Length:

0.500 inches single actuator

#### Flat Height:

0.187 inches single actuator

# Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

# 0.750 inches single actuator

**Overall Diameter:** 

2.125 inches

Individual Section Quantity:

1

**Operating Tempurature Range:** 

-65.0/+160.0 degrees fahrenheit

# Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

1 single section front

# **Throw Quantity:**

4 single section rear

# **Mounting Method:**

Threaded bushing single mounting facility

# Thready Qty Per Inch (tpi):

32 single mounting facility

# **Thread Size:**

0.469 inches single mounting facility

# Contact Voltage Rating In Volts:

28.0 dc at sea level

# **Rotor Through Connection Quantity:**

1 single section

# Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

# NSN 5930-00-651-2345

Rotary Switch - Page 2 of 2



**Terminal Type:** Tab w/screw **Contact Switching Action:** Breaks before makes single section rear **Switch Actuator Positioning Increment:** 90.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 15.0 amperes resistive load ac at sea level Style Designator: Tap, circular, bushing mount **Thread Series Designator:** Uns single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0