## NSN 5930-00-651-7899

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-651-7899

Body Style:
Hole mounted
Overall Length:
0.781 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.375 inches
Overall Width:
0.250 inches
Body Length:
0.781 inches
Body Width:
0.250 inches
Body Height:
0.356 inches
Unthreaded Mounting Hole Diameter:
0.098 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.302 inches
Maximum Voltage Rating In Volts:
125.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
1.0 ounces
Switch Actuating Force:
Between 3.0 ounces and 5.0 ounces
Actuator Movement:
Between 0.030 pretravel inches and 0.005 overtravel inches and 0.004 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac
Precious Material And Location:
Contacts silver
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a

## NSN 5930-00-651-7899

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0