

View Online at <https://aerobasegroup.com/nsn/5930-00-652-0840>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Overall Length:**

Between 0.866 inches and 0.886 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Overall Width:**

Between 0.336 inches and 0.356 inches

**Body Length:**

Between 0.866 inches and 0.886 inches

**Body Width:**

Between 0.336 inches and 0.356 inches

**Body Height:**

0.600 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.078 inches

**Actuator Height:**

0.070 inches

**Actuator Free Position Height:**

0.175 inches

**Maximum Voltage Rating In Volts:**

200.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 5.0 ounces and 17.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0