

View Online at <https://aerobasegroup.com/nsn/5930-00-652-0840>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Overall Length:

Between 0.866 inches and 0.886 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Overall Width:

Between 0.336 inches and 0.356 inches

Body Length:

Between 0.866 inches and 0.886 inches

Body Width:

Between 0.336 inches and 0.356 inches

Body Height:

0.600 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.078 inches

Actuator Height:

0.070 inches

Actuator Free Position Height:

0.175 inches

Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 5.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0