

View Online at <https://aerobasegroup.com/nsn/5930-00-653-3918>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.995 inches and 1.005 inches

Body Length:

Between 1.907 inches and 1.969 inches

Body Width:

Between 1.344 inches and 1.406 inches

Body Height:

0.830 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

Between 1.141 inches and 1.183 inches

Actuator Roller Diameter:

Between 0.344 inches and 0.406 inches

Actuator Roller Width:

Between 0.125 inches and 0.187 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Switch Release Force:

0.5 ounces

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.020 overtravel inches and 0.109 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0