

View Online at <https://aerobasegroup.com/nsn/5930-00-655-1512>

Body Style:

Hole mount

Overall Length:

2.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches

Overall Height:

2.219 inches

Overall Width:

1.500 inches

Body Length:

1.688 inches

Body Width:

1.500 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

0.875 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

440.0 ac and 30.0 dc

End Application:

Commerical utility cargo vehicle, hh/uh-1, uh-1 helicopters, support equipment b-52, f-106 aircraft, assult amphibious vehicle command (aavc-7a1), c-135 stratolifter aircraft, m-551 sheridan tank, blue ridge class lcc-19, carrier, pers m-113a2, m113a3.

Mounting Surface To Terminal End Distance:

Between 1.312 inches and 1.375 inches

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

30.000 amperes resistive dc and 18.000 amperes inductive dc and 50.000 amperes motor dc and 5.500 amperes resistive ac and 3.000 amperes inductive ac and 5.500 amperes motor ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0