

View Online at <https://aerobasegroup.com/nsn/5930-00-655-1523>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

1.141 inches

Overall Height:

2.288 inches

Overall Width:

0.641 inches

Bushing Length:

Between 0.450 inches and 0.490 inches

Body Length:

1.141 inches

Body Width:

0.641 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.235 inches and 0.245 inches

Actuator Height:

Between 0.660 inches and 0.720 inches

Actuator Position-action Relationship:

Up position maintained and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

220.0 ac and 250.0 dc

Mounting Surface To Terminal End Distance:

1.180 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary, two positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Test Data Document:

81349-mil-dtl-83731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0