

View Online at <https://aerobasegroup.com/nsn/5930-00-655-1759>

Thread Class:

3b all threaded hole

Overall Length:

3.480 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Body Length:

2.000 inches

Body Width:

2.000 inches

Longest Horizontal Distance Between Mounting Centers:

1.500 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between 32.0 degrees fahrenheit and 122.0 degrees fahrenheit

Mounting Method:

Bracket and threaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

34.00 pounds per square inch gage

Thread Size:

0.138 inches all threaded hole

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

10.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

4.00 deactuation point pounds per square inch gage and 6.00 actuation point pounds per square inch gage and 2.00 differential point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0