## NSN 5930-00-655-3488

Sensitive Switch - Page 1 of 2

**Terminal Type And Quantity:** 

6 screw



View Online at https://aerobasegroup.com/nsn/5930-00-655-3488

Hazardous Locations/environmental Protection:
Watertight
Switch Actuator Quantity:
1
Actuator Length:
1.500 inches
Actuator Style:
Roller arm
Actuator Height:
1.000 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.031 inches
Housing Length:
4.938 inches
Housing Bushing Length:
2.312 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.812 inches
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Switch Release Force:
8.0 inch-ounces
Switch Actuating Force:
125.0 inch-ounces
Actuator Movement:
11.0 pretravel degrees and 70.0 overtravel degrees and 12.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
25.000 amperes resistive dc and 25.000 amperes resistive ac
Special Features:
Spring return of switch lever

## NSN 5930-00-655-3488

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0