NSN 5930-00-656-2418

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-656-2418 **Thread Class:** 2b single mounting facility **Overall Length:** 3.390 inches **Overall Height:** 1.870 inches **Overall Width:** 1.280 inches First Flat Length: 0.570 inches single actuator Flat Height: 0.210 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.575 inches single actuator **Individual Section Quantity:** 5 **Longest Horizontal Distance Between Mounting Centers:** 0.780 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 0.592 inches single mounting facility **End Application:** B-52 aircraft **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.138 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Two position diagonal single mounting facility **Switch Actuator Indexing Position Quantity:** 3 single actuator **Shaft Type:** Round, flatted single actuator **Terminal Type:**

Wire lead

NSN 5930-00-656-2418

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load and 0.5 amperes inductive load dc at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A052b0