NSN 5930-00-656-5306

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-656-5306

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
6.938 inches
Overall Height:
3.396 inches
Overall Width:
1.438 inches
Case Material:
Metal
Actuator Style:
Round, stepped
Actuator Diameter:
1.000 inches
Actuator Height:
1.318 inches
Housing Height:
2.000 inches
Housing Length:
3.438 inches
Housing Width:
1.438 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.625 inches
Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
10.0 ounces
Switch Actuating Force:
Between 28.0 ounces and 54.0 ounces

Actuator Movement:

Between 0.078 pretravel inches and 0.187 overtravel inches and 0.005 differential inches

NSN 5930-00-656-5306

Sensitive Switch - Page 2 of 2



Contact	I oad	Current	Rating	Δt	Maximum	Rated	Voltage:
Contact	Luau	Current	Naumy	\neg	WIGNIIII	Nateu	VOILAGE.

3.000 amperes resistive dc and 5.000 amperes resistive ac and 1.200 amperes inductive ac

Terminal Type And Quantity:

2 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0