NSN 5930-00-658-3414

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-658-3414

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.563 inches **Overall Height:** 1.093 inches **Overall Width:** 0.952 inches **Shaft Diameter:** 0.125 inches single actuator **Shaft Length:** 0.438 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Pin at 3: 00 o'clock **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 4 single section front **Throw Quantity:** 2 single section rear **Mounting Method:** Threaded bushing single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.250 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 2 single actuator **Shaft Type:** Round single actuator **Terminal Type:**

Threaded stud

NSN 5930-00-658-3414Rotary Switch - Page 2 of 2



| Contact Switching Action: |
|---|
| Breaks before makes single section rear |
| Switch Actuator Positioning Increment: |
| 30.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 500.0 milliamperes resistive load ac at sea level |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Circular wafer, bushing mount |
| Thread Series Designator: |
| Unc single mounting facility |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A052b0