# NSN 5930-00-658-3416

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-658-3416

### **Thread Class:**

2a single mounting facility

### Thread Length:

0.250 inches single mounting facility

## **Overall Length:**

2.932 inches

#### **Overall Height:**

1.093 inches

**Overall Width:** 

0.952 inches

#### Shaft Diameter:

0.125 inches single actuator

#### Shaft Length:

0.438 inches single actuator

#### **Nonturn Device Radius:**

## 0.375 inches at 3: 00 o'clock

#### Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

6 each section front

#### **Throw Quantity:**

5 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### Thread Size:

0.250 inches single mounting facility

### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

5 single actuator

#### Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes each section rear

# NSN 5930-00-658-3416

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 1.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0